

Artisan

php artisan routes

php artisan controller:make UserController

// Migrations

php artisan migrate:make create_users_table

php artisan migrate:make create_users_table --create=users

php artisan migrate

php artisan migrate:rollback

php artisan migrate:refresh

// Seed

php artisan generate:seed posts

php artisan db:seed

php artisan migrate:refresh --seed

php artisan db:seed --class=PostsTableSeeder

// Generators

php artisan generate:resource post --fields="title:string, body:text"

php artisan generate:pivot categories users

Migrations

```
...
public function up(){
    Schema::create('users', function(Blueprint $table){
        $table->increments('id');
        $table->integer('role');
        $table->string('email')->unique();
        $table->string('password', 60);
        $table->rememberToken();
        $table->timestamps();
    });
}

public function down(){
    Schema::drop('users');
}
...
```

Seeds (faker)

```
...
User::create([
    'email' => $faker->email(),
    'password' => $faker->md5()
]);
...
```

Routes

Ruta simple

```
Route::get('/', function(){
    return View::make('hello');
});
```

Ruta amb paràmetres

```
Route::get('posts/{id}', function($id){
    return View::make('post.single')->with('id', $id);
});
```

Ruta Controlador + mètode

```
Route::get('post', 'PostController@show');
```

Ruta nominal

```
Route::get('post/all', array('uses' => 'PostController@all', 'as' =>
    'post.all'));
```

Ruta + validació RegEX

```
Route::get('post/{id}', array('uses' => 'PostController@single', 'as' =>
    'get.post.single'))->where('id', '[1-9][0-9]*');
```

Ruta POST

```
Route::post('post', array('uses' => 'PostController@create', 'as' =>
    'post.post.create'));
```

Ruta Resource

```
Route::resource('post', 'PostController');
Route::resource('post', 'PostController', array('except' => 'show'));
Route::resource('post', 'PostController', array('only' => 'show'));
```

Filtres

```
Route::get('post/create', array('uses' => 'PostController@create', 'as'
    => 'post.create', 'before' => 'auth'));
```

Grups

```
Route::group(array('before' => 'auth'), function(){
    // Route:: ...
    // Route:: ...
});
```



By **bernattorras**

Published 9th October, 2014.

Last updated 13th May, 2016.

Page 1 of 3.

Sponsored by **CrosswordCheats.com**

Learn to solve cryptic crosswords!

<http://crosswordcheats.com>

Routes (cont)

```
});
Prefixs
Route::group(array('prefix' => 'admin'), function(){
// Route:: ...
// Route:: ...
});
```

Blade functions

```
@if(count($posts))
@foreach($posts as $post)
<p>{{{ $post->title }}} </p>
@endforeach
@endif
```

Blade Layout

```
<!-- HTML -->
@include('partials.menu');
[...]
@yield('content');
[...]
@section('sidebar');
[...]
@show
```

Blade Template

```
@extends('layouts.default');
@section('content');
[...]
@stop
@section('sidebar')
@parent
[...]
@stop
```

Query Builder

```
// SELECT
$users = DB::table('users')->get();
$users = DB::table('users')->find(2);
$users = DB::table('users')->where('id',2)->get();
$users = DB::table('users')->where(array('id' => 2, 'email' => 'test@-
test.com'))->get();
$users = DB::table('users')->where('id',2)->orWhere('id', 3)->get();
$users = DB::table('users')->where(array('id' => 2, 'email' => 'test@-
test.com'))->get();
$users = DB::table('users')->where('id', '>', 1)->orderBy('id', 'asc')->t-
ake(2)->skip(2)->get();
$users = DB::table('users')->join('posts', 'users.id', '=', 'posts.user_
id')->get();
// Log
dd(DB::getQueryLog());
// INSERT
$data = array(
'email' => 'bernat.torras@uvic.cat',
'password' => '123456'
);
DB::table('users')->insert($data);
// UPDATE
$data = array(
'email' => 'bernat.torras@uvic.cat',
'password' => 'abc'
);
DB::table('users')->where('email', $data['email'])->update($data);
// DELETE
DB::table('users')->where('email', 'bernat.torras@uvic.cat')->delete();
```

Eloquent ORM

```
// SELECT
$posts = Post::all();
$posts = Post::find(2);
$posts = Post::where('title', 'LIKE', '%et%')->get();
$posts = Post::where('title', 'LIKE', '%et%')->take(1)->skip(1)->get();
// INSERT
$post = new Post;
$post->title = 'post1 title';
$post->body = 'post1 body';
```



By bernattorras

Published 9th October, 2014.

Last updated 13th May, 2016.

Page 2 of 3.

Sponsored by **CrosswordCheats.com**

Learn to solve cryptic crosswords!

<http://crosswordcheats.com>

Eloquent ORM (cont)

```
$post->save();  
// Insert amb vector de dades  
$data = array(  
    'title' => 'post2 title',  
    'body' => 'post2 body'  
);  
Post::create($data);  
// UPDATE  
$post = Post::find(1);  
$post->title('updated title');  
$post->save();  
// DELETE  
$post = Post::find(1);  
$post->delete();
```

Relacions BDD (Model)

```
class Post extends \Eloquent {  
    ...  
    public function user(){  
        return $this->belongsTo("User");  
    }  
    // hasMany  
    // hasOne  
    // belongsToMany  
}  
...  
}
```



By **bernattorras**

cheatography.com/bernattorras/

Published 9th October, 2014.

Last updated 13th May, 2016.

Page 3 of 3.

Sponsored by **CrosswordCheats.com**

Learn to solve cryptic crosswords!

<http://crosswordcheats.com>