Aurelia Getting Started Cheat Sheet

by Erik Hanchett (ErikCH) via cheatography.com/20589/cs/3750/

Quick Getting Started

1. npm install -g gulp
2. npm install -g jspm
3. jspm registry config github
4. Download skeleton-navigation https://github.com/aurelia/skeleton-navigation/releases
5. Change directories to skeleton directory
6. npm install
7. jspm install -y
8. gulp watch

Make sure to have node installed first

Templating Examples

.one-way	<ma rkd own -editor value.o ne -wa y="m ark dow n"></ /ma rkd own -ed ito r>
.two-way	<ma rkd own -editor value.t wo -wa y="m ark dow n"></ /ma rkd own -ed ito r>
.bind	<input type="t ext " value.b ind ="f irs tNa me"> <a href.b ind ="ur l">A ure lia
trigger	<button click.t ri gge r="s ayH ell o() " >Say Hello< /bu tto n>
delegate	<button click.d el ega te= " sayHello() ">Say Hello</bu tto n>
call	<div touch.c al l="s ayH ell o() " >Say Hello< /bu tto n>
string interp-olation	</ div>
ref	<input type="t ext " ref="na me"> ${name.value}
select	<option repeat.fo r="color of colors " value.b ind ="c olo r">${co lor }</ opt ion>
inner html	<div innerh tml.bi nd= " htm lPr ope rty " ></ div> <div innerh tml ="${ htm lPr ope rty }"></ /di v>
textCo-ntent	<div textco nte nt.b in d="s tri ngP rop ert y"></ /di v> <div textco nte nt= " ${s tri ng P rop ert y}"> </d iv>
style	<div style.b in d="s tyl eSt rin g"></ /di v> <div style.b in d="s tyl eOb jec t"></ /di v>

Template Example Code

```
<template>
    <se cti on>
        <h2 >${ hea din g}
< /h2>
        <form role="f orm "
submit.de leg ate ="we lco -
me( )">
```

Template Example Code (cont)

```
>      <div class="form-group">
        <label for="fn">First Name</label>
        <input type="text" value.bind="firstNa-
me" class="form-control" id="fn" placehold-
er="first name">
      </div>
      <div class="form-group">
        <label for="ln">Last Name</label>
        <input type="text" value.bind="last-
Name" class="form-control" id="ln" placeh-
older="last name">
      </div>
      <div class="form-group">
        <label>Full Name</label>
        <p class="help-block">${fullName |
upper}</p>
      </div>
      <button type="submit" class="btn btn-
default">Submit</button>
    </form>
  </section>
</template>
```

All templates must start with <template> and end with </template>

HTTP Client Methods

Install	jspm install aurelia-http-client
createReq-uest(uri)	Custom configure individual requests
delete(uri)	HTTP Delete request
get(uri)	HTTP Get Request
head(uri)	HTTP Head Request

HTTP Client Methods (cont)

jsonp(uri, callbackPara-meterName='jsoncal-lback')	Sends JSONPReqe-ustMessage
put(uri, content)	HTTP Put Request
patch(uri, content)	HTTP Patch Request
post(uri, content)	HTTP Post Request

The result of sending a message is a promise, it has the following properties. response, responseType, content, headers, statusCode, statusText, isSuccess, reviver, requestMesssage

HTTP Client Example (Flickr)

```
import {HttpClient} from
'aurelia-http-client';
var url = 'http://api.flickr.com/services/feeds/photos_public.gne?tags=ra-
ini er&tagmode=any&format=json';
export class Flickr{
    static inject() { return
[HttpClient]; }
    constructor(http){
        this.heading =
'Flickr';
        this.images = [];
        this.http = http;
    }
    activate(){
        return this.http.js-
onp(url).then(response => {
            this.images =
response.content.items;
        });
    }
    canDeactivate(){
        return confirm('Are you
sure you want to leave?');
```


By **Erik Hanchett** (ErikCH)
cheatography.com/erikch/
www.ProgramWithErik.com

Published 29th March, 2015.
Last updated 11th May, 2016.

Sponsored by **CrosswordCheats.com**
Learn to solve cryptic crosswords!
http://crosswordcheats.com

Cheatography

Aurelia Getting Started Cheat Sheet

by Erik Hanchett (ErikCH) via cheatography.com/20589/cs/3750/

HTTP Client Example (Flickr) (cont)

```
> }
}
```

jsonp requet returns a promise

Extending HTML Behaviours

Attached Beahviours	Adds new behavior or functionality to existing HTML element
Custom Elements	New tags to HTML Markup
Template Controllers	Convert Dom into inert HTML template

Behavior Examples

```
//Attached Behavior (jquery)
<div show.b ind ="is Sav ing "
class= " spi nne r">< /di v>
import {Behavior} from 'aurel -
ia- tem pla ting';
export class Show {
    static metada ta(){
        return Behavior
            .at tac hed Beh avi -
or( 'show')
            .wi thP rop ert y(' -
value', 'value Cha nged',
'show');
    }
//Custom Element
<te mpl ate>
        <re quire from="./ sa y-
h ell o">< /re qui re>
        <input type="t ext "
ref="na me">
        <sa y-hello to.bin -
d="n ame.va lue " ></ say -he -
llo>
</t emp lat e>
import {Behavior} from 'aurel -
ia- tem pla ting';
```

Behavior Examples (cont)

```
> export class SayHello {
  static metadata(){
    return Behavior
      .customElement('say-hello')
      .withProperty('to');
  }
  speak(){
    alert('Hello ${this.to}!');
  }
}
//Template Controllers
li repeat.for="customer of customers">${-
customer.fullName}</li>
```

Routing Activation Lifecycle

canActivate(params, queryString, routeConfig)	Hook to be navigated too
activate(params, queryString, routeConfig)	Custom logic before view-model is displayed
canDeactivate()	Router can navigate from view?
deactivate()	Logic as you are being navigated from

Router Example

```
import {Router} from 'aurelia-
router';
import bootstrap from 'boots -
trap';
export class App {
    static inject() { return
[Router]; }
    con str uct or( router) {
        thi s.r outer = router;
        thi s.r out er.c on -
fig ure (config => {
            con fig.title =
'Aurelia';
            con fig.map([
               { route: ['','w -
elc ome'], moduleId: './wel -
come', nav: true, title: 'We -
lcome' },
               { route:
'flickr', moduleId: './fli ckr',
nav: true },
               { route:
'child -ro uter', moduleId:
'./chi ld- rou ter', nav: true,
title: 'Child Router' }
            ]);
        });
    }
}
~
```

DI Example

```
import {HttpClient} from
'aurelia-http-client';
export class Custom erD etail{
        static inject() { return
[HttpC lient]; }
        con str uct or( http){
                thi s.http =
http;
        }
}
```

By **Erik Hanchett** (ErikCH)
cheatography.com/erikch/
www.ProgramWithErik.com

Published 29th March, 2015.
Last updated 11th May, 2016.
Page 2 of 2.

Sponsored by **CrosswordCheats.com**
Learn to solve cryptic crosswords!
http://crosswordcheats.com