

### Basics

**Docker-Compose:** is a tool for defining and running multi-container Docker applications. With Compose, you use a YAML file to configure your application's services. Then, with a single command, you create and start all the services from your configuration.

Need to go to yml file directory to successfully run the docker-compose commands.

docker-compose start wordpress\_db :it will only start 1 service  
but docker-compose start : will start all the services  
similar is the case with other commands.

### docker-compose start

Starts an existing service container.

### docker-compose stop

-t, --timeout specify a shutdown timeout in seconds.(default: 10)

Stops running containers without removing them. They can be started again with `docker -co mpose start`.

### docker-compose pause

Pauses running containers of a service. They can be unpaused with `docker-compose unpause`

### docker-compose unpause

Unpauses paused containers of a service.

### docker-compose restart

Restarts all stopped and running services.

### docker-compose ps

-q, --quiet Only display IDs

Shows list of containers for a service.

### docker-compose logs

-f, --follow Follow log output.

Displays log output from services.

### docker-compose top

View the processes running within each service container.

### Network

```
# creates a custom network called frontend
networks:
  fro ntend:
```

### Dependencies

```
# makes the db service available as the hostname database
# (implies depends_on)
links:
  - db:database
  - redis
# make sure db is alive before starting
depends_on:
  - db
```

### docker-compose.yml

```
version: "3.7"
services:
  wor dpr ess_db:
    con tai ner _name: " wor dpr ess _db "
    image: " mys ql: 5.7 "
    vol umes:
      - ~/dock ers /wo rdp res s/.d at a/w -
ord pre ss_db: /va r/l ib/ mysql
    env iro nment:
      MYS QL_ USER: gaurav
      MYS QL_ PAS SWORD: victory
      MYS QL_ DAT ABASE: db
      MYS QL_ RAN DOM _RO OT_ PAS SWORD: '1'
    net works:
      - wordpr ess _ne twork
    ports:
      - 3307:3306
  wor dpr ess _web:
    con tai ner _name: " wor dpr ess _we b"
    image: " wor dpr ess "
    vol umes:
      - ~/dock ers /wo rdp res s/.d at a/w -
ord pre ss _web :/v ar/ www /html
```



By Gaurav Pandey  
(gauravpandey44)

Published 21st September, 2019.  
Last updated 23rd September, 2019.  
Page 1 of 3.

Sponsored by **CrosswordCheats.com**  
Learn to solve cryptic crosswords!  
<http://crosswordcheats.com>

### docker-compose.yml (cont)

```
> environment:
  WORDPRESS_DB_HOST: wordpress_db
  WORDPRESS_DB_USER: gaurav
  WORDPRESS_DB_PASSWORD: victory
  WORDPRESS_DB_NAME: db
networks:
  - wordpress_network
ports:
  - 8080:80
depends_on:
  - wordpress_db
networks:
  wordpress_network:
```

### docker-compose rm

Removes stopped service containers. By default, anonymous volumes attached to containers are not removed. You can override this with -v. To list all volumes, use docker volume ls.

- f, --force – Don't ask to confirm the removal
- s, --stop – Stop the containers, if required, before removing
- v – Remove any anonymous volumes attached to containers

### docker-compose pull

Pulls an image associated with a service defined in a docker-compose.yml file, but does not start containers based on those images.

### docker compose up

|                                                            |                                                     |
|------------------------------------------------------------|-----------------------------------------------------|
| docker-compose up                                          | use docker-compose.yml                              |
| docker-compose -f <filename.yml> -f <filenamelocal.yml> up | use custom yaml files                               |
| -d, --detach                                               | background detached mode                            |
| --build                                                    | forcefully Build images before starting containers. |
| --no-build                                                 | skips the image build process                       |

### docker compose up (cont)

|                     |                                                                                             |
|---------------------|---------------------------------------------------------------------------------------------|
| --force-recreate    | Recreate containers even if their configuration and image haven't changed.                  |
| --no-color          | Produce monochrome output.                                                                  |
| --scale SERVICE=NUM | Scale SERVICE to NUM instances. Overrides the scale setting in the Compose file if present. |

docker-compose up is used to start a project. It tries to automate a series of operations including building a mirror, (re)creating a service, starting a service, and associating a service-related container. It also builds the images if the images do not exist and starts the containers:

### docker-compose down

Stops containers and removes containers, networks, volumes, and images

By default, the only things removed are:

- Containers for services defined in the Compose file
  - Networks defined in the `networks` section of the Compose file
  - The default network, if one is used
- created by `up`. Networks and volumes defined as `external` are never removed.
- use -v to remove volumes also along with other things

### docker-compose version

Prints the version of docker-compose.

### docker-compose push

Pushes images for services to their respective registry/repository

### docker-compose run

Runs a one-time command against a service. For example, the following command starts the web service and runs bash as its command :

```
docker-compose run wordpress_db bash
```



By Gaurav Pandey  
(gauravpandey44)

Published 21st September, 2019.  
Last updated 23rd September, 2019.  
Page 2 of 3.

Sponsored by **CrosswordCheats.com**  
Learn to solve cryptic crosswords!  
<http://crosswordcheats.com>

### docker-compose config

Validate and view the Compose file.

### docker-compose kill

Forces running containers to stop by sending a SIGKILL signal.

### docker-compose bundle

A Dockerfile can be built into an image, and containers can be created from that image. Similarly, a docker-compose.yml can be built into a distributed application bundle

### docker-compose build

only builds the images, does not start the containers:

### Building

```
web:
  # build from Dockerfile
  build: .
  # build from custom Dockerfile
  build:
    context: ./dir
    dockerfile: Dockerfile.dev
  # build from image
  image: ubuntu
  image: ubuntu :14.04
  image: tutum/inf luxdb
  image: example-registry:4000/postgres
  image: a4bc65fd
```

### Ports

```
ports:
  - "3000"
  - "8000:8000" # guest:host
  # expose ports to linked services (not to host)
  expose: ["3000"]
```

### Commands

```
# command to execute
command: bundle exec thin -p 3000
command: [bundle, exec, thin, -p, 3000]
# override the entrypoint
entrypoint: /app/start.sh
entrypoint: [php, -d, vendor/bin/phpunit]
```

### Environment variables

```
# environment vars
environment:
  RACK_ENV: development
environment:
  - RACK_ENV=development
# environment vars from file
env_file: .env
env_file: [.env, development.env]
```



By Gaurav Pandey  
(gauravpandey44)

Published 21st September, 2019.  
Last updated 23rd September, 2019.  
Page 3 of 3.

Sponsored by [CrosswordCheats.com](https://crosswordcheats.com)  
Learn to solve cryptic crosswords!  
<http://crosswordcheats.com>