

Document Outline

<!DOCTYPE>	Version of (X)HTML
<html>	HTML document
<head>	Page information
<body>	Page contents
<!-- -->	Comments

Page Information

<base />	Base URL
<meta />	Meta data
<title>	Title
<link />	link to CSS
<style>	Insert CSS
<script>	Insert JavaScript

Document Structure

<h[1-6]>	Heading
-> h1 most important, h6 least important	
<div>	Page section
	Inline section
<p>	Paragraph
 or 	Line break
<hr /> or <hr>	Horizontal rule

Anchors (link)

	anchor (link)
----------------	---------------

Absolute links - "https://www.example.com"

Relative links - "example.html"

Root-relative links - "/page"

	Email link
	Phone dial link

	Anchor
---------------	--------

	Link to anchor
------------------	----------------

	specifies link location
---------------------	-------------------------

Anchors (link) (cont)

_blank - in a new window or tab
 _self - in the same window/tab (default)
 _parent - in the parent frame
 _top - in the full body of the window
 frameName - in a named frame

specifies extra information about an element that shown as a tooltip text when the mouse moves over the element.

<a download> or

Specifies that the target will be downloaded. The value of the attribute will be the name of the downloaded file. If the value is omitted, the original filename is used.

Specifies the language of anchor linked

specifies relationship with current document

Favicon (shortcut icon)

<link rel="shortcut icon" type="image/x-icon" href="favicon.ico" />

Include an icon in the title.

Uniform Resource Locators (URL)

Scheme	Short for	Used for
http	HyperText Transfer Protocol	Common web pages. Not encrypted
https	Secure HyperText Transfer Protocol	Secure web pages. Encrypted
ftp	File Transfer Protocol	Downloading or uploading files
file		A file on your computer

Form

<form action="URL" method="get | post"> Form

<label for="id"> Label

<input /> form input

attribute: **maxlength** maximum length of input

attribute: **name** name for input

attribute: **placeholder** placeholder for input



By KenlandTan

Published 9th February, 2019.

Last updated 17th January, 2019.

Page 1 of 4.

Sponsored by **Readable.com**

Measure your website readability!

<https://readable.com>

Form (cont)

attribute: type ="text"	Text Input
attribute: type ="password"	Password Input
attribute: type ="hidden"	Hidden input
attribute: type ="date"	Date Input
attribute: type ="file"	File input
attribute: type ="submit"	Submit button
attribute: type ="image" src="URL" width=" " height=" "	Image submit button
attribute: type ="email"	Email input
attribute: type ="url"	URL input
attribute: type ="search"	Search input

Radio button and Checkbox

attribute: type ="radio" value=" "	Radio button
attribute: type ="checkbox" value=" "	Checkbox
attribute: checked ="checked"	pre-checked input

Drop Down List Box

<select>	Drop Down List Box
<select size="#" multiple="multiple">	Multiple Select Box
<option value=" ">	option for drop-down list
attribute: required ="required"	Form Validation
<button type="button">	button
<fieldset>	Grouping Form Elements
<legend>	caption

<meta> name Attribute

```

<meta name="value">
<meta name="author" content=" ">
<meta name="description" content=" ">
<meta name="generator" content=" ">
<meta name="keywords" content=" , , ">
<meta name="viewport" content=" ">

```

Other Tags

<embed type=" " src=" ">	External application
<nav>	navigation section
<header>	Header section
<footer>	Footer section
attribute: contenteditable ="true"	Allow editable areas
attribute: spellcheck ="true"	Allow spell check areas

Lists

**** Ordered list

<ol type="1|a|A|i|I">

1 Default value Decimal numbers 1,2,3,4
a Alphabetically ordered (lowercase) a,b,c,d
A Alphabetically ordered (uppercase) A,B,C,D
i Roman Numerals (lowercase) i,ii,iii,iv
I Roman Numerals (uppercase) I,II,III,IV

<ol start="number">

Define the number the list will start with

<li value="number">

Overwrite the number the list will display

**** Unordered list

**** List item

<dl> Definition list

<dt> Definition term

<dd> Term description

Text Formatting

 or 	Important text (bold)
 or <i>	Emphasized text
<small>	smaller text
<mark>	highlighted text
	deleted text
<ins>	Inserted text
<sub>	subscripted text
<sup>	superscripted text



By KenlandTan

Published 9th February, 2019.
Last updated 17th January, 2019.
Page 2 of 4.

Sponsored by **Readable.com**
Measure your website readability!
<https://readable.com>

Quotation and Citation Elements

<code><q></code>	Short quotation
<code><blockquote></code> <code>cite="URL"></code>	Long quotation
<code><abbr title=" "></code>	Abbreviation
<code><address></code>	Address
<code><cite></code>	Citation
<code><bdo dir="value"></code> value = rtl or ltr	Bi-directional override
<code><pre></code>	Preformatted text
<code><dfn></code>	Defining a term
<code><code></code>	Code
<code><var></code>	Variable
<code><kbd></code>	Keyboard input
<code><samp></code>	Sample output

Tables

<code><table></code>	Table
<code><caption></code>	Caption
<code><thead></code>	Table header
<code><tbody></code>	Table body
<code><tfoot></code>	Table footer
<code><colgroup></code>	Column group
<code><col></code>	Column
<code><tr></code>	Table row
<code><th></code>	Header cell
<code><td></code>	Table cell
<code><td colspan="#"></code>	Spanning column
<code><td rowspan="#"></code>	Spanning row

Image Map

```

<map name="shapes">
  <area shape="polygon" coords=" , , ">
  <area shape="rectangle" coords=" , , ">
  <area shape="circle" coords=" , , ">
</map>
```

Images

<code></code>	Image
<code><figure></code>	Contain images and caption
<code><figcaption></code>	caption of image

Attribute of image:

```
src="URL" alt="..." title="..."
width="px" height="px"
```

Common Character Entities

<code>&#34;</code>	"	Quotation mark
<code>&#38;</code>	&	Ampersand
<code>&#60;</code>	<	Less than
<code>&#62;</code>	>	Greater than
<code>&#64;</code>	@	"At" symbol
<code>&#128;</code>	€	Euro
<code>&#149;</code>	•	Small bullet
<code>&#153;</code>	™	Trademark
<code>&#163;</code>	£	Pound
<code>&#160;</code>		Non-breaking space
<code>&#169;</code>	©	Copyright symbol

Core Attributes

<code>class=" "</code>	Indicates Class (non-unique)
<code>id=" "</code>	Indicates ID (unique)

The only restrictions on the value of an id and class are:

- it must not contain any space characters
- it must contain at least one character
- It must begin with a letter, which may followed only by:
 - letters (A-Z/a-z),
 - hyphens ("-"),
 - colons (":"),
 - digits (0-9),
 - underscores ("_"),
 - periods (".")



By KenlandTan

Published 9th February, 2019.

Last updated 17th January, 2019.

Page 3 of 4.

Sponsored by **Readable.com**

Measure your website readability!

<https://readable.com>

JavaScript

```
<script src="URL"></script>
```

Include JS

```
<script src="URL" async> </script>
```

Once JS is fully downloaded, it will interrupt the HTML parsing in order to parse the Javascript file

```
<script src="URL" defer> </script>
```

HTML parsing will only be performed once the HTML is fully parsed.

```
<noscript> JavaScript disabled </noscript>
```

The content of <noscript> is displayed whenever Javascript is disabled for the current page.

Media Elements

```
<audio controls>
```

 Audio

```
<source src=" " type="audio/mpeg">
```

```
<video width=" " height=" " controls>
```

 Video

```
<source src=" " type="video/mp4">
```

Browser will display the word between media tags when media is not supported.

<meta> http-equiv Attribute

```
<meta http-equiv="content-type/default-style/refresh">
```

```
<meta http-equiv="content-type" content="text/html; charset=UTF-8">
```

```
<meta http-equiv="default-style" content="title of preferred stylesheet">
```

```
<meta http-equiv="refresh" content="300">
```



By KenlandTan

cheatography.com/kenlandtan/

Published 9th February, 2019.

Last updated 17th January, 2019.

Page 4 of 4.

Sponsored by **Readable.com**

Measure your website readability!

<https://readable.com>