

cache <pre>\$ bower cache <command> [<args>]</pre> Manage bower cache	info <pre>\$ bower info <package> \$ bower info <package> [<property>] \$ bower info <package> #<version> [<property>]</pre> Displays overall information of a package or of a particular version.	lookup <pre>\$ bower lookup <name></pre> Look up a package URL by name	version <pre>\$ bower version [<newversion> major minor patch]</pre> Run this in a package directory to bump the version and write the new data back to the bower.json file
cache clean <pre>\$ bower cache clean \$ bower cache clean <name> [<name> ...] \$ bower cache clean <name> #<version> [<name> #<version> ..]</pre> Cleans cached packages	install <pre>\$ bower install [<options>] \$ bower install <endpoint> [<endpoint> ..] [<options>]</pre> Installs the project dependencies or a specific set of endpoints.	prune <pre>\$ bower prune</pre> Uninstalls local extraneous packages	Options
cache list <pre>\$ bower cache list \$ bower cache list <name> [<name> ...]</pre> Lists cached packages	link <pre>\$ bower link \$ bower link <name> [<local name>]</pre> The link functionality allows developers to easily test their packages.	register <pre>\$ bower register <name> <url></pre> Register a package	allow-root <pre>--allow-root</pre> Allows running commands as root.
help <pre>\$ bower help <command></pre> Display help information about Bower	login <pre>\$ bower login</pre> Authenticate with GitHub and store credentials. Required to unregister packages.	search <pre>\$ bower search \$ bower search <name></pre> Finds all packages or a specific package.	force <pre>-f, --force</pre> Makes various commands more forceful
home <pre>\$ bower home \$ bower home <package> \$ bower home <package> #<version></pre> Opens a package homepage into your favorite browser.	list <pre>\$ bower list [<options>]</pre> List local packages and possible updates.	uninstall <pre>\$ bower uninstall <name> [<name> ..] [<options>]</pre> Uninstalls a package locally from your bower_components directory	json <pre>-j, --json</pre> Output consumable JSON
init <pre>\$ bower init</pre> Interactively create a bower.json file		update <pre>\$ bower update <name> [<name> ..] [<options>]</pre> Updates installed packages to their newest version according to bower.json	log-level <pre>-l, --log-level</pre> What level of logs to report
		unregister <pre>\$ bower unregister <package></pre> Unregisters a package	offline <pre>-o, --offline</pre> Do not use network connection
			quiet <pre>-q, --quiet</pre> Only output important information
			silent <pre>-s, --silent</pre> Do not output anything, besides errors



verbose

-V, --verbose

Makes output more verbose



By **pertrai1**
cheatography.com/pertrai1/

Published 6th December, 2015.
Last updated 13th May, 2016.
Page 2 of 2.

Sponsored by **CrosswordCheats.com**
Learn to solve cryptic crosswords!
<http://crosswordcheats.com>