

Positional Arguments

USERNAMES One or more usernames to check with social networks.

Scan Arguments

-verbose/-v/--debug/-d Display debugging information and metrics.

-tor/-t Make requests over TOR. Increases runtime.

-unique-tor/-u Make requests over TOR with new TOR circuit after each request. *Substantially* increases runtime.

-site [SITE_NAME] Limit analysis to just the listed sites.

-proxy/-p [PROXY_URL] Make requests over a proxy.

-json/-j [JSON_FILE] Load data from a JSON file or an online, valid, JSON file.

-timeout [TIMEOUT] Time (in seconds) to wait for response to requests.

-local/-l Force the use of the local data.json file.

Output Arguments

-folder-output/-fo [FOLDEROUTPUT] If using multiple usernames, the output of the results will be saved to this folder.

-output/-o [OUTPUT] If using a single username, the output of the results will be saved to this file.

-csv Create a CSV file.

-print-all Output sites where the username was not found.

print-found Output sites where the username was found.

-no-color Don't color the terminal output.

Misc. Arguments

verbose/-v/--debug/-d Display debugging information and metrics.

-version Display version information and dependencies.

-browse/-b Browse to all results on default browser.

Examples

sherlock john_doe Search for only one user.

sherlock john_doe jane_doe Search for multiple users.

sherlock --timeout 4 john_doe Wait for four seconds between requests and responses.

sherlock --site reddit.com john_doe Check only a particular site(s) for the username's presence.

sherlock -t john_doe Onion route requests.

sherlock --csv john_doe Create a CSV file for the results.

sherlock -o 'john_doe_instances.txt' john_doe Send results to an output file.

sherlock -fo John john_doe, johndoe Send results to folder with a file for each username specified.

